

SPECIFICATION

Pick up Element 1/3" Color CCD image sensor

Resolution Standard

Min. Illumination 0.5 Lux / F2.0

S/N Ratio More than 48dB (AGC off)

Electronic Shutter 1/60 (1/50) to 1/100,000 sec.

Lens Mount C/CS mount changeable

IRIS Mode D.D / V.D / AES

AGC Auto

Flickerless On/ Off selectable

White Balance ATW

Video Output 1.0Vp-p composite, 75Ω

Microphone YES

Power Source (±10%) DC12V

Current Consumption (10%) 80mA

Dimensions (mm)** 108(L) x 62(W) x 50(H)



SPECIFICATION	521
Pick up Element	1/3" SONY Color CCD image sensor
Number of Pixels	768(H) x 494(V) <NTSC> / 752(H) x 582(V) <PAL>
Resolution	420 TV lines
Min. Illumination	0.5Lux / F1.2
S/N Ratio	More than 48dB (AGC off)
Electronic Shutter	1/60 to 1/100,000 second (NTSC); 1/50 to 1/100,000 second (PAL)
Lens Mount	C / CS mount changeable
Iris Mode	AES / D.D. / V.D. selectable
BLC	On / Off
AGC	Normal / Max selectable
Flickerless	On (FL1/100(120)) / Off selectable
White Balance	ATW / HOLD
CRLESS	On / Off
Video Output	1.0Vp-p composite, 75Ω
Audio	Audio
Power Source	AC24V / AC100V ~ 240V ± 10% / DC12V ± 10%
Power Consumption	3 W Max. (AC24V) 2.4 W Max. (AC100V ~ 240V ± 10%) 95mA ± 10% (DC12V)
Dimension (mm)	107.3(L) * 65.5(W) * 50(H)

FEATURES

Satisfactory minimum illumination of 0.5 Lux/F2.0

Audio function supported

Auto Electronic Shutter built-in

Signal-to-noise ratio of 48dB